



~ NOTES ~

1. DELINEATOR SHALL BE MEASURED AND PAID FOR AT THE CONTRACT UNIT PRICE EACH, AND SHALL INCLUDE ALL MATERIALS AND LABOR NECESSARY FOR ONE COMPLETE INSTALLATION.
2. THE DELINEATORS SHALL BE YELLOW IN COLOR WHEN THE BARRIER IS PLACED IN THE MEDIAN AND/OR ON THE LEFT SIDE OF THE DRIVING LANE. THE DELINEATORS SHALL BE WHITE IN COLOR WHEN THE BARRIER IS PLACED ON THE RIGHT SIDE OF THE DRIVING LANE.
3. DELINEATORS SHALL BE APPLIED 300 FEET IN ADVANCE OF AND THROUGHOUT THE LENGTH OF ALL BRIDGES THAT DO NOT HAVE FULL WIDTH SHOULDERS. SPACING ON BRIDGES AND 300 FEET IN ADVANCE OF BRIDGES SHALL BE 50 FEET ON CENTERS. THE FIRST DELINEATOR ON THE GUARDRAIL SHALL BE PLACED 50 FEET FROM THE DELINEATOR AT THE END OF THE BRIDGE. DELINEATORS SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.
4. DELINEATORS SHALL NOT BE INSTALLED WITHIN THE PAY LIMITS OF THE END TREATMENT.
5. WHEN CONCRETE BARRIERS EXTEND ACROSS NARROW SHOULDER WIDTH STRUCTURES IN LIEU OF STEEL BEAM GUARDRAIL, DELINEATORS SHALL BE INSTALLED AT SAME VERTICAL ALIGNMENT AS ON THE GUARDRAIL AND DELINEATORS SHALL COMPLY WITH CURRENT STANDARD DRAWING RBM-020 .
6. GUARDRAIL DELINEATORS SHALL COMPLY WITH CURRENT STANDARD DRAWING RBR-055.
- ⑦ SEE SECTION 718 OF THE CURRENT STANDARD SPECIFICATIONS FOR "OBJECT MARKER TYPE 2".

USE WITH CUR. STD. DWGS.  
RBM-020 RBR-055

BID ITEMS AND UNIT TO BID

DELINEATORS FOR CONCRETE BARRIERS	
DELINEATOR FOR BARRIER - WHITE	EACH
DELINEATOR FOR BARRIER - YELLOW	EACH
DELINEATORS ON GUARDRAIL	
DELINEATOR FOR GUARDRAIL M/W	EACH
DELINEATOR FOR GUARDRAIL M/Y	EACH
OBJECT MARKER TYPE 2	EACH
STEEL POST TYPE 1	LF

PRIMARY USE:  
(PAVEMENT REHABILITATION PROJECTS)