



1. THE COST OF CONSTRUCTING RUMBLE STRIPS SHALL BE INCLUDED IN THE UNIT BID PRICE FOR JOINTED PLAIN CONCRETE PAVEMENT.
2. SEE CUR. STD. DWG. RPS-010 FOR JOINT SYMBOLS AND DETAILS.
3. AFTER FINAL FINISHING OF THE PAVEMENT, CORRUGATIONS FOR RUMBLE STRIPS SHALL BE FORMED AT THE INTERVALS SHOWN INTO THE PLASTIC CONCRETE.
4. THE CORRUGATIONS SHALL BE ROUNDED RATHER THAN PEAKED, WITH THE TOP FLUSH WITH THE SHOULDER OR MEDIAN SLOPE.
5. THE TROUGH SHALL BE TAILED OUT, SO AS TO PROVIDE POSITIVE DRAINAGE.
- ⑥ JOINTED PLAIN CONCRETE SHOULDER OR MEDIAN (UNDOWELLED) IS DETAILED. WHEN JOINTED PLAIN CONCRETE SHOULDER OR MEDIAN (DOWELLED) IS REQUIRED REFER TO CUR. STD. DWG. RPM-145 FOR DETAIL.

USE WITH CUR. STD. DWGS.
RPM-145, RPS-010

