## 120" PIPE

PIPE		CIRCULAR PIPE COVER HEIGHTS IN FEET 4																							
DIA.	PIPE TYPE	2-	5-	10-	15-	20-	25-	30-	35-	40-	45-	50-	55-	60-	65-	70-	75-	80-	85-	90-	95-	100-	105-	110-	115-
(IN)		5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115	120
	3"x1" CSPHS (1)						10 GA	,		, , , , , , , , , , , , , , , , , , , ,		, , , , , , , , , , , , , , , , , , , ,													
120	3" x 1" CSPLS (1)				10 GA	١.												///							
	5"x1" CSPHS (1)					10 GA	GA.																		
	6"x2" CSPLSSB (1)		10 GA		8 GA.			GA.	5 GA.	3 GA.		, , , , , , , , , , , , , , , , , , , ,	, , , , , , , , , , , , , , , , , , , ,	1 GA.	, , , , , , , , , , , , , , , , , , , ,	, , , , , , , , , , , , , , , , , , , ,									
	3"x1" CAPHS	'x1" CAPHS						_																	
	9"x2½" CAPLSSB	, , , , , ,	10 G	Α.	8 GA.	7 GA.	5 GA.	3 GA.		1 GA.									///						
	RCP (9)							///																	
								///																	
								///																	
				///																					
		2-	5-	10-	15-	20-	25-	30-	35-	40-	45-	50-	55-	60-	65-	70-	75-	80-	85-	90-	95-	100-	105-	110-	
		5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115	120

## ~ NOTES ~

- 1 GAGES FOR CORRUGATED STEEL PIPE ITEMS SHOWN ARE BASED ON ALUMINUM-COATED TYPE 2 STEEL AS PER AASHTO M-274. ALUMINUM COATED TYPE 2 STEEL IS ONLY PERMITTED IN Ph RANGES OF 5 TO 9.
- 2. WHEN CORRUGATED STEEL PIPE IS ZINC COATED (GALVANIZED) THE GAGE SHALL BE ONE GAGE HEAVIER THAN SHOWN IN THE TABLES.
- 3. CONTRARY TO NOTE 2, GAGES FOR 6" x 2" CSPLSSB ARE SHOWN FOR ZINC COATED (GALVANIZED).
- (4) SEE CUR. STD. DWG. DRAWING RDI-001 FOR EXPLANATION OF COVER HEIGHTS LESS THAN 2 FEET.
- 5. CSP, CAP, SRS AND SRA ARE SHOWN IN GAGE.
- 6. MAXIMUM COVER HEIGHT MEASURED FROM TOP OF PIPE TO SUBGRADE ELEVATION SHALL GOVERN GAGE OF PIPE TO BE USED FOR ENTIRE LENGTH OF PIPE INSTALLATION.
- 7. ALL CIRCULAR STRUCTURAL PLATE SHALL BE 5% VERTICALLY ELONGATED.
- 8. SEE CUR. STD. DWG. RDI-035 FOR COATINGS, LININGS AND PAVINGS FOR NON-STRUCTURAL PIPE.
- 9 SEE CUR. STD. DWGS. RDI-021 AND RDI-026 FOR RCP COVER HEIGHT AND BEDDING REQUIREMENTS.

USE WITH CUR. STD. DWGS. RDI-001 RDI-021 RDI-026 RDI-035

## LEGEND

CSPHS: CORRUGATED STEEL PIPE WITH HELICAL

LOCK SEAM OR HELICAL WELDED SEAM (HELICAL CORR.)

CSPLS: CORRUGATED STEEL PIPE WITH LONGITUDINAL RIVETED OR SPOT WELDED SEAM (ANNULAR CORR.)

CSPLSSB: CORRUGATED STEEL PIPE WITH LONGITUDINAL SEAMS WITH STEEL BOLTS (ANNULAR CORR.)

CAPHS: CORRUGATED ALUMINUM ALLOY PIPE WITH HELICAL

LOCK SEAM (HELICAL CORR.)

CAPLSSB: CORRUGATED ALUMINUM ALLOY PIPE WITH LONGITUDINAL SEAMS WITH STEEL BOLTS (ANNULAR CORR.)

RCP: CIRCULAR REINFORCED CONCRETE PIPE