



PLAN VIEW

~ NOTES ~

1. TRANSVERSE CONTRACTION JOINTS SHALL BE SPACED 15'-0" ON CENTER AND SAWED TO A MINIMUM DEPTH OF ONE THIRD OF THE PAVEMENT THICKNESS (T/3) OR 4", WHICHEVER IS LESS. ALL TRANSVERSE CONTRACTION AND TRANSVERSE EXPANSION JOINTS SHALL REQUIRE LOAD TRANSFER ASSEMBLIES AS DETAILED ON THE PLANS OR STANDARD DRAWINGS.
 2. JOINT SPACING AND TYPE, AT BRIDGE ENDS, SHALL BE REQUIRED AS SHOWN ON THE PLANS OR CUR. STD. DWG. RPS-010.
 3. TRANSVERSE CONSTRUCTION JOINTS SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 501.03.17 OF THE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, CURRENT EDITION.
 4. SEE CUR. STD. DWG. RPS-010 FOR JOINT SYMBOLS AND DETAILS.
- USE WITH CUR. STD. DWG.
RPS-010

REVISION DATE: 12/01/2015
REVISION NUMBER: 0

SUBMITTED *William S. Leland* 12-01-2015
DIVISION DIRECTOR DATE
APPROVED *Shawn* 12-01-2015
STATE HIGHWAY ENGINEER DATE

PAVEMENT



COMMONWEALTH OF KENTUCKY
DEPARTMENT OF HIGHWAYS



JOINTED PLAIN CONCRETE PAVEMENT

JOINTED PLAIN CONCRETE PAVEMENT

STANDARD DRAWING NUMBER
RPN-015-05