



CHANNELIZED INTERSECTION ON A TWO DIRECTIONAL TWO LANE FACILITY

LEGEND

BI-DIRECTIONAL PAVEMENT MARKER (YELLOW)

MONO-DIRECTIONAL PAVEMENT MARKER (WHITE)

CURBED OR FLUSH MEDIAN

MARKINGS (YELLOW)

MARKINGS (WHITE)

~ NOTES ~

- MARKERS INSTALLED ALONG DASHED YELLOW CENTERLINES SHALL BE PLACED BETWEEN AND IN LINE WITH THE SKIPS.
- MARKERS INSTALLED ALONG EDGE LINES OR CHANNELIZING LINES SHALL BE PLACED SO THAT THE NEAR EDGE OF THE GROOVE IS NO MORE THAN 1" FROM THE NEAR EDGE OF THE LINE.
- MARKERS SHALL NOT BE INSTALLED ON TOP OF THE PAVEMENT JOINT. OFFSET MARKERS A MINIMUM OF 2" FROM THE PAVEMENT JOINT. ENSURE THAT THE FINISHED LINE OF MARKERS IS STRAIGHT WITH MINIMAL LATERAL DEVIATION. MARKERS MAY BE ELIMINATED OR PLACEMENT ADJUSTED AT THE DISCRETION OF THE ENGINEER.

BID ITEMS AND UNITS TO BID  
 06610 - INLAID PAVEMENT MARKER - MW  
 06612 - INLAID PAVEMENT MARKER - BY

EACH  
 EACH  
 DRAWING NOT TO SCALE  
 USE WITH CUR. STD. DWG.  
 TPM-205



COMMONWEALTH OF KENTUCKY  
 DEPARTMENT OF HIGHWAYS

INLAID PAVEMENT MARKER ARRANGEMENT CHANNELIZED INTERSECTION

STANDARD DRAWING NUMBER  
 TPM-145-04

PERMANENT

SUBMITTED *Jim Ballinger* 08-11-2025  
 DIVISION DIRECTOR  
 APPROVED *Jim Ballinger* 08-11-2025  
 STATE HIGHWAY ENGINEER

REVISION DATE: 08/11/2025  
 REVISION NUMBER: 0