



ARRANGEMENT "E" (DIVIDED HIGHWAY WITH CURB WITHIN 8' OF DRIVING LANE)

~ NOTES ~

1. MARKERS INSTALLED ALONG LANE LINES SHALL BE PLACED BETWEEN AND IN LINE WITH THE SKIPS.
- ② MARKERS INSTALLED ALONG EDGE LINES SHALL BE PLACED SO THAT THE NEAR EDGE OF THE GROOVE IS NO MORE THAN 1" FROM THE NEAR EDGE OF THE LINE.
3. MARKERS SHALL NOT BE INSTALLED ON TOP OF THE PAVEMENT JOINT. OFFSET MARKERS A MINIMUM OF 2" FROM THE PAVEMENT JOINT. ENSURE THAT THE FINISHED LINE OF MARKERS IS STRAIGHT WITH MINIMAL LATERAL DEVIATION. MARKERS MAY BE ELIMINATED OR PLACEMENT ADJUSTED AT THE DISCRETION OF THE ENGINEER.
4. MARKERS SHALL BE INSTALLED AT 40' SPACING ALONG SOLID WHITE AUXILIARY LANES. MARKER COLOR SHALL MATCH THE MARKERS INSTALLED ALONG THE WHITE LANE LINES.

BID ITEMS AND UNIT TO BID

06610 - INLAID PAVEMENT MARKER - MW	EACH
06611 - INLAID PAVEMENT MARKER - MY	EACH

LEGEND

	MONO-DIRECTIONAL PAVEMENT MARKER (YELLOW)
	MONO-DIRECTIONAL PAVEMENT MARKER (WHITE)
	MARKINGS (YELLOW)
	MARKINGS (WHITE)

DRAWING NOT TO SCALE



COMMONWEALTH OF KENTUCKY  
DEPARTMENT OF HIGHWAYS

INLAID PAVEMENT MARKER ARRANGEMENTS MULTI LANE ROADWAYS

STANDARD DRAWING NUMBER  
TPM-110-04

PERMANENT

REVISION DATE: 08/11/2025  
REVISION NUMBER: 0

SUBMITTED: 08-11-2025  
DIVISION DIRECTOR

APPROVED: 08-11-2025  
STATE HIGHWAY ENGINEER